


**ULTRAnchor - SELECTION TABLE**  
**AS THE FIRST BOW ANCHOR FOR HEAVY DUTY APPLICATIONS**

January - 2011



## BOAT WEIGHT AND LENGTH ULTRAnchor CAN HOLD (MAX.)

ULTRA ANCHOR WEIGHT (kg) - (lbs)	Sail Boat		Power Boat		Catamaran			Recommended DIN 766 Chain Diameter (mm)
	Boat Weight (ton)	Boat Length (m) (feet)	Boat Weight (ton)	Boat Length (m) (feet)	Sail Catamaran Weight (ton)	Power Catamaran Weight (ton)	Boat Length (m) (feet)	
5 - 11	1,2	6 - 20	1,6	5,5 - 18	0,8	1	6 - 20	5
8 - 18	2	7 - 23	2,7	6,4 - 21	1,3	1,7	7 - 23	6
12 - 26	3,6	8,6 - 28	4,8	8 - 26	2,4	3	8,6 - 28	6
16 - 35	7	11 - 36	9,3	10,4 - 34	4,7	6	11 - 36	6 - 8
21 - 46	12	12,8 - 42	16	13,1 - 43	8	10	12,8 - 42	8
27 - 60	18	14,5 - 48	24	15,8 - 52	12	15	14,5 - 48	8 - 10
35 - 77	26	16 - 53	35	18,6 - 61	17,3	22	16 - 53	10
45 - 100	37	17,8 - 58	50	23,2 - 76	24,7	31	17,8 - 58	10 - 12
60 - 132	55	20 - 66	73	25 - 82	37	46	20 - 66	12 - 13
80 - 176	85	22,4 - 74	112	30 - 98	57	71	22,4 - 74	13
100 - 220	120	24,4 - 80	160	33,5 - 110	80	100	24,4 - 80	13 - 14
130 - 290	180	27 - 89	240	38,4 - 126	120	150	27 - 89	14 - 16
160 - 350	245	30 - 98	330	44,2 - 145	165	210	30 - 98	16
200 - 440	330	33 - 108	440	48 - 157	220	280	33 - 108	18 - 20

- Anchor selection should be made based on the largest anchor required between boat weight or boat length.

- ULTRAnchors FIT NICELY AS BOW OR STERN ANCHORS. THEY ARE NOT SUITABLE TO SIDE HAWSE HOLES!